

Óaðiè-ãñèèà àaííúà àñeíððííúð àæèààòææé iaðàíáííái òíèà ñ ê.ç. ðíðíðí ñáðèè 4À (IP23

Óaðiè-ãñèèà àaííúà ýææòðíáæèààòææé iaðàíáííái òíèà ñ ê.ç. ðíðíðí ñáðèè 4À, eñííeíáíèà ïí ñòáíáíè çàùèòú IP23, ñííñíá íòèàà

Á	ÒeíÁ	áæèààòæy	Á Ðí,Á	Á	êÀðÁ	Á ïðe ïííeíæéúííe íarpóçeáÁ	Mmax/MíÁ	í/í	Mmin/MíÁ					
Á	Á ní,Á	í6/íeíÁ	Á	@, %Á	cos Í†	Á	1	2	3	4	5	6	7	8
10	Á	Á Ñeíððííáy ÷ãñòíðà áðàùáíeý	4,25Á·10-2	Á	4Á160í2Ó3	3000 íá/íeíÁ	Á	4Á160S2Ó3	22,0	2915	88,0			
1,3	1,0	7,0				30,0	2915	90,0	0,91	2,2	1,3			
1,0	7,0	5,5Á·10-2	Á		4Á180S2Ó3	37,0	2945	91,0	0,91	2,2	1,2	1,0		
7,0	8,0Á·10-2	Á			4Á180í2Ó3	45	2945	91,0	0,91	2,2	1,3	1,0	1,0	7,0
9,25Á·10-2	Á				4Á200í2Ó3	55,0	2940	91,0	0,90	2,5	1,3	1,0	7,0	
16,0Á·10-2	Á	4AH200L2Ó3	75,0	2940	92,0	0,90	2,5	1,3	1,0	7,0				
19,0Á·10-2	Á	4Á225í2Ó3	90,0	2945	92,0	0,88	2,2	1,2	1,0	7,0				
23,8Á·10-2	Á	4AH250S2Ó3	110,0	2950	93,0	0,86	2,2	1,2	1,0	7,0				
44,3Á·10-2	Á	4Á250í2Ó3	132,0	2945	93,0	0,88	2,2	1,2	1,0	7,0				
49,5Á·10-2	Á	4AH280S2Ó3	160,0	2960	94,0	0,90	2,2	1,2	1,0	6,5				
77,5Á·10-2	Á	4Á280í2Ó3	200,0	2960	94,5	0,90	2,2	1,2	1,0	6,5	1,03			
Á	4ÁÇ15í2Ó3	250,0	2970	94,5	0,91	2,1	2,1	1,0	0,9	6,0	1,7	Á		
4AH355S2Ó3	315,0	2970	94,5	0,92	2,1	1,0	0,9	7,0	2,38	Á				
4Á355í2Ó3	400,0	2970	95,0	0,92	2,1	1,0	0,9	7,0	2,85	Á		Á Ñeíððííáy		
1500 íá/íeíÁ	Á	AH160S4Ó3	18,5	1450	88,5	0,87	2,1	1,3	1,0	6,5				
9,25Á·10-2	Á	4Á160í4Ó3	22,0	1458	90,0	0,88	2,1	1,3	1,0	6,5				
11,8Á·10-2	Á	4AH180S4Ó3	30,0	1465	90,0	0,84	2,2	1,2	1,0	6,5				
17,8Á·10-2	Á	4Á180í4Ó3	37,0	1470	90,5	0,89	2,2	1,2	1,0	6,5				
21,8Á·10-2	Á	4Á200í4Ó3	45,0	1475	91,0	0,89	2,5	1,3	1,0	6,5				
34,5Á·10-2	Á	4AH200L4Ó3	55,0	1475	92,0	0,89	2,5	1,3	1,0	6,5				
42,3Á·10-2	Á	4Á225í4Ó3	75,0	1475	92,5	0,89	2,2	1,2	1,0	6,5				
61,8Á·10-2	Á	4AH250S4Ó3	90,0	1480	93,5	0,89	2,2	1,2	1,0	6,5				
88,3Á·10-2	Á	4Á250í4Ó3	110,0	1475	93,5	0,89	2,2	1,2	1,0	6,5				
95,8Á·10-2	Á	4AH280S4Ó3	132,0	1470	93,0	0,89	2,0	1,2	1,0	6,0				
1,83	Á	4Á280í4Ó3	160,0	1470	93,5	0,90	2,0	1,2	1,0	6,0	2,13	Á		
	4AH315S4Ó3	200,0	1475	94,0	0,91	2,0	1,2	0,9	6,0	3,15	Á			
4Á315í4Ó3	250,0	1475	94,0	0,91	2,0	1,2	0,9	6,0	3,7	Á				
4AH355S4Ó3	315,0	1485	94,5	0,91	2,0	1,0	0,9	7,0	5,75	Á				
4Á355í4Ó3	400,0	1485	94,5	0,91	2,0	1,0	0,9	7,0	7	Á		Á Ñeíððííáy ÷ãñòíðà		
1000 íá/íeíÁ	Á	4AH180S6Ó3	18,5	975	87,0	0,85	2,0	1,2	1,0	6,0				
18,8Á·10-2	Á	4Á180í6Ó3	22,0	975	88,5	0,87	2,0	1,2	1,0	6,0				
23,5Á·10-2	Á	4Á200í6Ó3	30,0	975	90,0	0,88	2,1	1,3	1,0	6,0				
37,7Á·10-2	Á	4Á200L6Ó3	37,0	980	90,5	0,88	2,1	1,3	1,0	6,5				
43,0Á·10-2	Á	4Á225í6Ó3	45,0	980	91,0	0,87	2,0	1,2	1,0	6,5				
70,3Á·10-2	Á	4AH250S6Ó3	55,0	985	92,5	0,87	2,0	1,2	1,0	6,5				
1,09	Á	4Á250í6Ó3	75,0	985	93,0	0,87	2,0	1,2	1,0	7,0	1,4	Á		
	4AH280S6Ó3	90,0	980	92,5	0,89	2,0	1,2	1,0	6,0	2,5	Á			
4Á280í6Ó3	110,0	980	92,5	0,89	2,0	1,2	1,0	6,0	2,88	Á				
4AH315S6Ó3	132,0	985	93,0	0,89	2,0	1,2	1,0	6,0	4,45	Á				
4Á315í6Ó3	160,0	985	93,5	0,89	2,0	1,2	1,0	6,0	5,13	Á				
4AH355S6Ó3	200,0	985	94,0	0,90	2,0	1,2	1,0	6,0	7,8	Á			4Á355í6Ó3	
250,0	985	94,0	0,90	2,0	1,2	1,0	6,0	9,5	Á		Á Ñeíððííáy ÷ãñòíðà áðàùáíeý			
Á	4AH180S8Ó3	15,0	730	86,0	0,80	1,9	1,2	1,0	5,5	23,2Á·10-2	Á			
	4Á180í8Ó3	18,5	730	87,5	0,80	1,9	1,2	1,0	5,5	29,8Á·10-2	Á			
4Á200í8Ó3	22,0	730	89,0	0,84	2,0	1,3	1,0	5,5	49,0Á·10-2	Á				
4AH200L8Ó3	30,0	730	89,S	0,82	2,0	1,3	1,0	5,5	58,3Á·10-2	Á				
4Á225í8Ó3	37,0	735	90,0	0,81	1,9	1,2	1,0	5,5	82,5Á·10-2	Á				
4AH250S8Ó3	45,0	740	91,0	0,81	1,9	1,2	1,0	5,5	1,19	Á		4Á250í8Ó3		
55,0	735	92,0	0,81	1,9	1,2	1,0	6,0	1,4	Á	4AH280S8Ó3	75,0			
735	92,0	0,85	1,9	1,2	1,0	5,5	3,0	Á	4Á280í8Ó3	90,0	735			
92,S	0,86	1,9	1,2	1,0	5,5	3,38	Á	4AH315S8Ó3	110,0	735	93,0			
0,86	1,9	1,2	1,0	5,5	6,08	Á	4Á315í8Ó3	132,0	735	93,0	0,86			
1,9	1,2	1,0	5,0	7,0	Á	4AH355S8Ó3	160,0	740	93,5	0,86	1,9			
1,2	1,0	5,5	9,75	Á	4Á355í8Ó3	200,0	740	94,0	0,86	1,9	1,2	1,0		
5,5	11,9	Á	Á Ñeíððííáy ÷ãñòíðà áðàùáíeý	600 íá/íeíÁ	Á	4AH280S10Ó3	45,0	58						
1,8	1,0	1,0	5,5	3,23	Á	4Á780í10Ó3	55,0	585	90,S	0,81	1,8			

1,0	1,0	5,5	3,75	Â	4ÂÍÇ15S10Ó3	75.0	590	91,0	0,82	1,8	1,0		
0,9	5,5	5,63	Â	4ÂÍ315Ì10Ó3	90.0	590	91,S	0,82	1,8	1,0	0,9		
5,5	6,63	Â	4AH355S1ÍÓ3	110.0	590	92,0	0,83	1,8	1,0	0,9	5,5		
9,68	Â	4ÂÍ355Ì10Ó3	132.0	590	92,5	0,83	1,8	1,0	0,9	5,5	11	Â	
Ñèíòðííày ÷ àñòìòà àðàùáàèy 500 íá/ìéí													
5,5	5,63	Â	4ÂÍ315Ì12Ó3	75.0	490	91	0,78	1,8	1	0,9	5,5	9,68	Â
Â	4AH355S12Ó3	90.0	490	91,5	0,77	1,8	1	0,9	5,5	9,68	Â		
4ÂÍ355Ì12Ó3	110	490	92	0,77	1,8	1	0,9	5,5	11	Â			

Â

Â