

Òáóíe÷ãñeã àáííúá àñeíðíííúð ýeáeððíããeãàòãeãe ñãðeè 4À (4ÀÊ) ñ òàçíùì ðíðíðì (IP44)

Òáóíe÷ãñeã àáííúá àñeíðíííúð ýeáeððíããeãàòãeãe ñãðeè 4À Á ñ òàçíùì ðíðíðì, íããóããáíúá, ï ñòáíáíe çàùeòù IP44. Ñãðey ïð ãðàùáíey.

Ñòàòíðù ýóíe ñãðeè óíeðeðeðíááíú ñ áãeãàòãeyíe ïñíáííáí eññíeíáíey. Ðíòíðù ïðe áùñíòà ïñe áðàùáíey H=160Á-200 ïì eíáðò áñù ááóðñeíeíóð íáííðeó. Íáííðeà ðíðíðà ñíããeíýòñý ï ñòáíà Á «çããããÁ», eííóù ïíãeëð-áíú e eííòãeðíùì eíeyüòàì. Ò.e. á ýóíe ñãðeè ïð

ÊÏÄ, %	cos ï	Sí, %	Mmax/Míí	Óíe ð-ðà, Á	Íáíðýããáíeà ð-ðà, B	Ìãññà, Á	éã	1	2
6	7	8	9	Ñeíððííáý ÷ãñòíðà áðàùáíey 1500	íá/íeí	4AK160S4Ó3	11	86,5	0,86
22	305	160		4AK160M4Ó3	14	88,5	0,87	4,0	3,5
			18	89,0	0,88	3,5	4,0	38	295
								250	250
90,0	0,87	2,5	4,0	45	340	305		4AK200L4Ó3	30
									90,5
4,0	55	350	325					4AK225í4Ó3	37
									90,0
415			45	91,0	0,88	3,0		3,0	170
									230
4AK250SB4Ó3	55	90,5	0,90	3,0	3,0	170	200	595	4AK250í4Ó3
									71
91,5	0,86	2,5	3,0	170	250	640			Ñeíððííáý ÷ãñòíðà áðàùáíey 1000
									íá/íeí
82.5	0,77	5,0	3,5	18	300	170		4AKI60M6Ó3	10,0
									84.5
3,8	20	310	200						0,76
									4,5
240				4AK180M6Ó3	13,0	85.5	0,80	4,5	4,0
									25
									325
22,0	88,0	0,80	3,5	3,5	45	330	315		4AK225í6Ó3
									30,0
3,5	2,5	150	140	405					89,0
									0,85
150	540			4AK250S6Ó3	37,0	89,0	0,84	3,5	2,5
									165
									4AK250í6Ó3
									45,0
									90,5
									0,87
									3,0
									2,5
									160
									180
									600
									Ñeíð
									÷ãñòíðà áðàùáíey 750
									íá/íeí
									4AK160S8Ó3
									5,5
									80,0
									0,70
									6,5
									2,5
									14
									300
									170
									4AK160í8Ó3
									7,5
									82,0
									0,70
									6,0
									3,0
									16
									290
									200
									4AK180í8Ó3
									11,0
									85,5
									4AK200í8Ó3
									15,0
									86,0
									0,70
									3,5
									3,0
									40
									300
									320
									4AK200L8Ó3
									18,5
									86,0
									0,73
									3,5
									3,0
									400
									4AK250S8Ó3
									30,0
									4AK22SM8Ó3
									22,0
									87,0
									0,82
									4,5
									2,2
									140
									102
									400
									4AK250S8Ó3
									30,0
									88,5
									0,81
									4,0
									2,2
									155
									125
									540
									4AK250í8Ó3
									37,0
									89,0
									0,80
									3,5
									595